

# F 15 O Race Fuel

## Safety Data Sheet

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : F 15 O

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Fuel

#### 1.3. Details of the supplier of the safety data sheet

Fuel Factory LLC  
4431 William Penn Hwy  
Murrysville, PA 15668  
(353) 151-3673

#### 1.4. Emergency telephone number

Ambipar Response Emergency Phone Number:  
1-800-219-8391 / Local +1 385-264-7545

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

|                           |      |
|---------------------------|------|
| Flam. Liq. 1              | H224 |
| Acute Tox 1 (Oral)        | H300 |
| Acute Tox. 1 (Dermal)     | H310 |
| Acute Tox. 2 (Inhalation) | H330 |
| Skin Irrit. 2             | H315 |
| Repr. 1                   | H360 |
| STOT SE 3                 | H336 |
| STOT RE 2                 | H373 |
| Asp. Tox. 1               | H304 |
| Aquatic Chronic 1         | H410 |
| Aquatic Acute 1           | H400 |

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Hazard statements (GHS-US) :

: Danger  
: H224 - Extremely flammable liquid and vapor  
H225 - Highly flammable Liquid and vapor  
H226 - Flammable liquid and vapor  
H227 - Combustible liquid  
H300 - Fatal if swallowed  
H304 - May be fatal if swallowed and enters airways  
H310 - Fatal in contact with skin  
H312+H332 - Harmful in contact with skin or if inhaled  
H315 - Causes skin irritation  
H330 - Fatal if inhaled  
H336 - May cause drowsiness or dizziness  
H360 - May damage fertility or the unborn child  
H361 - Suspected of damaging fertility or the unborn child  
H373 - May cause damage to organs through prolonged or repeated exposure  
H410 - Very toxic to aquatic life with long lasting effects  
H400 - Very toxic to aquatic life

# F 15 O Race Fuel

## Safety Data Sheet

### Precautionary statements (GHS-US)

: P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical/ventilating/lighting/equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P260 - Do not breathe dust/fume/gas/mist/vapors/spray  
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray  
P264 - Wash thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area  
P273 - Avoid release to the environment  
P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P301+P310 - IF SWALLOWED: immediately call a POISON CENTER or doctor/physician  
P302+P352 - IF ON SKIN: Wash with plenty of soap and water  
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - IF INHALED: remove victim to fresh air and keep at rest in a position comfortable for breathing  
P308+P313 - IF exposed or concerned: Get medical advice/attention  
P312 - Call a POISON CENTER/doctor/physician if you feel unwell  
P314 - Get medical advice and attention if you feel unwell  
P331 - If swallowed, do NOT induce vomiting  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P362 - Take off contaminated clothing and wash before reuse  
P370+P378 - In case of fire: Use CO<sub>2</sub>, dry chemical, foam (AFFF/ATC) or water spray for extinction  
P391 - Collect spillage  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS-US)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

| Name                          | Product identifier | %      | Classification (GHS-US)   |
|-------------------------------|--------------------|--------|---|
| 2-Methoxy-2-Methylpropane     | (CAS No) 1634-04-4 | 5 - 35 | Flam. Liq. 2, H225<br>Skin Irrit. 2, H315   |
| Methyl Benzene<br>(Component) | (CAS No) 108-88-3  | 0 - 10 | Flam. Liq. 2, H225<br>Skin Irrit. 2, H315<br>Repr. 2, H361<br>STOT SE 3, H336<br>STOT RE 2, H373            |
| Dimethylbenzene               | (CAS No) 1330-20-7 | 0 - 10 | Flam. Liq. 3, H226<br>Acute Tox. 4 (Dermal), H312<br>Acute Tox. 4 (Inhalation), H332<br>Skin Irrit. 2, H315 |
| 2-Methylbutane                | (CAS No) 78-78-4   | 5 - 15 | Flam. Liq. 1, H224<br>STOT SE 3, H336<br>Asp. Tox. 1, H304  |

# F 15 O Race Fuel

## Safety Data Sheet

|                          |                   |         |  |
|--------------------------|-------------------|---------|--|
| Tetraethylplumbane       | (CAS No) 78-00-2  | ≤ 0.05  | Flam. Liq. 4, H227<br>Acute Tox. 1 (Oral), H300<br>Acute Tox. 1 (Dermal), H310<br>Acute Tox. 2 (Inhalation), H330<br>Repr. 1A, H360<br>STOT RE 2, H373<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410 |
| 2,2,4 - Trimethylpentane | (CAS No) 540-84-1 | 25 - 70 | Flam. Liq. 2, H225<br>Asp. Tox. 1, H304<br>Skin Irrit. 2, H315<br>STOT SE 3, H336  |

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

|                                       |  |
|---------------------------------------|--|
| First-aid measures after inhalation   | : Remove person to fresh air. If not breathing, administer CPR or artificial respiration. Get immediate medical attention.   |
| First-aid measures after skin contact | : After contact with skin, wash immediately with plenty of water and soap. If skin reddening or irritation develops, seek medical attention.   |
| First-aid measures after eye contact  | : Immediately flush the eyes with plenty of water for at least 15 minutes while holding eyelids apart to ensure flushing of the entire surface of the eye. Continue flushing for an additional 15 minutes if a physician is not immediately available. Seek medical attention, preferably an ophthalmologist, immediately. |
| First-aid measures after ingestion    | : If the material is swallowed, get immediate medical attention or advice. DO NOT induce vomiting unless directed to do so by medical personnel.   |

#### 4.2. Most important symptoms and effects, both acute and delayed

|                                      |  |
|--------------------------------------|--|
| Symptoms/injuries after inhalation   | : Breathing high concentrations may be harmful. May cause central nervous system depression or effects. Symptoms may include headache, excitation, euphoria, dizziness, incoordination, drowsiness, light-headedness, blurred vision, fatigue, tremors, convulsions, loss of consciousness, coma, respiratory arrest and death, depending on the concentration and duration of exposure. Breathing high concentrations of this material, for example, in a confined space or by intentional abuse, can cause irregular heartbeats which can cause death. |
| Symptoms/injuries after skin contact | : Contact may cause reddening, itching and inflammation.   |
| Symptoms/injuries after eye contact  | : Contact may cause pain and severe reddening and inflammation of the conjunctiva. Effects may become more serious with repeated or prolonged contact.   |
| Symptoms/injuries after ingestion    | : May cause irritation of the mouth, throat and gastrointestinal tract. May cause central nervous system depression or effects. Symptoms may include salivation, pain, nausea, vomiting and diarrhea. Exposure may also cause central nervous system symptoms similar to those listed under "Inhalation"   |

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

|                                |   |
|--------------------------------|---|
| Suitable extinguishing media   | : CO2, dry chemical, foam (AFFF/ATC) or water spray |
| Unsuitable extinguishing media | : None.   |

#### 5.2. Special hazards arising from the substance or mixture

|                  |  |
|------------------|--|
| Fire hazard      | : Extremely flammable liquid and vapor.  |
| Explosion hazard | : In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. Vapors may travel long distances along ground before igniting/flashing back to vapor source. |

#### 5.3. Advice for firefighters

|                                |  |
|--------------------------------|--|
| Protection during firefighting | : Firefighters should wear full protective gear. |
|--------------------------------|--|

# F 15 O Race Fuel

## Safety Data Sheet

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

No additional information available

##### 6.1.2. For emergency responders

No additional information available

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : If possible, stop flow of product.  
Methods for cleaning up : Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillage into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

#### 6.4. Reference to other sections

No additional information available

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Comply with all applicable EPA, OSHA, NFPA and consistent state and local requirements. Use appropriate grounding and bonding practices. Store in properly closed containers that are appropriately labeled and in a cool well-ventilated area. Do not expose to heat, open flames, strong oxidizers or other sources of ignition. Do not cut, drill, grind or weld on empty containers since they may contain explosive residues. Avoid skin contact. Exercise good personal hygiene including removal of soiled clothing and prompt washing with soap and water.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

#### 7.3. Specific end use(s)

Fuel

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

| 2-Methoxy-2-Methylpropane (1634-04-4) |                          |         |
|---------------------------------------|--------------------------|---------|
| USA ACGIH                             | ACGIH TWA (ppm)          | 50 ppm  |
| Methyl Benzene (108-88-3)             |                          |         |
| USA ACGIH                             | ACGIH TWA (ppm)          | 20 ppm  |
| USA OSHA                              | OSHA PEL (TWA) (ppm)     | 200 ppm |
| USA OSHA                              | OSHA PEL (Ceiling) (ppm) | 300 ppm |

# F 15 O Race Fuel

## Safety Data Sheet

| Dimethylbenzene (1330-20-7)  |                                     |                         |
|------------------------------|-------------------------------------|-------------------------|
| USA ACGIH                    | ACGIH TWA (ppm)                     | 100 ppm                 |
| USA ACGIH                    | ACGIH STEL (ppm)                    | 150 ppm                 |
| Dimethylbenzene (1330-20-7)  |                                     |                         |
| USA OSHA                     | OSHA PEL (TWA) (mg/m <sup>3</sup> ) | 435 mg/m <sup>3</sup>   |
| USA OSHA                     | OSHA PEL (TWA) (ppm)                | 100 ppm                 |
| 2-Methylbutane (78-78-4)     |                                     |                         |
| USA ACGIH                    | ACGIH TWA (ppm)                     | 600 ppm                 |
| Tetraethylplumbane (78-00-2) |                                     |                         |
| USA ACGIH                    | ACGIH TWA (mg/m <sup>3</sup> )      | 0.1 mg/m <sup>3</sup>   |
| USA OSHA                     | OSHA PEL (TWA) (mg/m <sup>3</sup> ) | 0.075 mg/m <sup>3</sup> |

### 8.2. Exposure controls

|                                  |   |
|----------------------------------|---|
| Appropriate engineering controls | : Local exhaust and general ventilation must be adequate to meet exposure standards.                              |
| Hand protection                  | : Wear impervious gloves to minimize skin contact.  |
| Eye protection                   | : Safety glasses. Wear splash goggles if splashing is likely.   |
| Skin and body protection         | : Wear suitable working clothes.  |
| Respiratory protection           | : If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection. |

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|  |                      |
|--|----------------------|
| Physical state                             | : Liquid             |
| Odor                                       | : Strong hydrocarbon |
| Odor threshold                             | : No data available  |
| pH   | : Neutral            |
| Relative evaporation rate (butylacetate=1) | : No data available  |
| Melting point                              | : No data available  |
| Freezing point                             | : No data available  |
| Initial boiling point                      | : <150°F             |
| Flash point                                | : -40°F              |
| Self ignition temperature                  | : No data available  |
| Decomposition temperature                  | : No data available  |
| Flammability (solid, gas)                  | : No data available  |
| Vapor pressure                             | : No data available  |

|                                 |                     |
|---------------------------------|---------------------|
| Relative vapor density at 20 °C | : No data available |
| Specific gravity                | : .710              |
| Solubility                      | : Negligible.       |
| Log Pow                         | : No data available |
| Log Kow                         | : No data available |
| Viscosity, kinematic            | : No data available |
| Viscosity, dynamic              | : No data available |
| Explosive properties            | : No data available |
| Oxidizing properties            | : No data available |
| Explosive limits                | : No data available |

### 9.2. Other information

# F 15 O Race Fuel

## Safety Data Sheet

VOC content : 100 %

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

#### 10.3. Possibility of hazardous reactions

Will not occur.

#### 10.4. Conditions to avoid

Heat, flames, and other ignition sources.

#### 10.5. Incompatible materials

Strong oxidizing agents.

#### 10.6. Hazardous decomposition products

Combustion produces carbon monoxide, aldehydes, aromatic and other hydrocarbons.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Harmful in contact with skin. Harmful if inhaled.

| <b>2-Methoxy-2-Methylpropane (1634-04-4)</b> |                        |
|--|------------------------|
| LD50 oral rat                                | 4 g/kg                 |
| LD50 dermal rabbit                           | > 10000 mg/kg          |
| LC50 inhalation rat (ppm)                    | 23576 ppm/4h           |
| ATE US (oral)                                | 4000000.00000000 mg/kg |

  

| <b>Methyl Benzene (108-88-3)</b> |                     |
|----------------------------------|---------------------|
| LD50 oral rat                    | 636 mg/kg           |
| LD50 dermal rabbit               | 8390 mg/kg          |
| LC50 inhalation rat (mg/l)       | 12.5 mg/l/4h        |
| ATE US (oral)                    | 636.00000000 mg/kg  |
| ATE US (dermal)                  | 8390.00000000 mg/kg |

  

| <b>Dimethylbenzene (1330-20-7)</b> |                     |
|------------------------------------|---------------------|
| LD50 oral rat                      | 4300 mg/kg          |
| LC50 inhalation rat (mg/l)         | 47635 mg/l/4h       |
| ATE US (oral)                      | 4300.00000000 mg/kg |
| ATE US (dermal)                    | 1100.00000000 mg/kg |

  

| <b>Tetraethylplumbane (78-00-2)</b> |  |
|-------------------------------------|--|
| LC50 inhalation rat (mg/l)          | 850 mg/m <sup>3</sup> (Exposure time: 1 h) |
| ATE US (oral)                       | 5.00000000 mg/kg body weight               |
| ATE US (dermal)                     | 5.00000000 mg/kg body weight               |
| ATE US (gases)                      | 100.00000000 ppmV/4h                       |
| ATE US (vapors)                     | 0.50000000 mg/l/4h                         |
| ATE US (dust, mist)                 | 0.05000000 mg/l/4h                         |

  

| <b>2,2,4 Trimethylpentane (540-84-1)</b> |  |
|--|--|
| LD50 oral rat                            | >5,000 mg/kg                             |
| LD50 dermal rabbit                       | >2000 mg/kg                              |
| LC50 inhalation rat (ppm)                | >33.52 mg per liter (Exposure time: 4 h) |

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : May cause genetic defects.

# F 15 O Race Fuel

## Safety Data Sheet

Carcinogenicity : May cause cancer.

| <b>2-Methoxy-2-Methylpropane (1634-04-4)</b> |  |
|--|--|
| IARC group                                   | 3 - Not classifiable   |
| <b>Methyl Benzene (108-88-3)</b>             |  |
| IARC group                                   | 3 - Not classifiable   |
| <b>Dimethylbenzene (1330-20-7)</b>           |  |
| IARC group                                   | 3 - Not classifiable   |
| <b>Tetraethylplumbane (78-00-2)</b>          |  |
| IARC group                                   | 3 - Not classifiable   |
| <b>2,2,4 Trimethylpentane (540-84-1)</b>     |  |
| IARC group                                   | No Ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. |
| ACGIH  | No Ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH             |
| National Toxicity Program (NTP) Status       | No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP                  |

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure): May cause damage to organs through prolonged or repeated exposure. Affected organs include: blood, kidneys, reproductive system, liver, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Aspiration hazard : May be fatal if swallowed and enters airways.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

| <b>2-Methoxy-2-Methylpropane (1634-04-4)</b> |  |
|--|--|
| LC50 fish 1                                  | 672 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])           |
| EC50 Daphnia 1                               | 542 mg/l (Exposure time: 48 h - Species: Daphnia magna)                                |
| EC50 other aquatic organisms 1               | > 800 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)                    |
| LC50 fish 2                                  | 929 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])                 |
| EC50 other aquatic organisms 2               | 184 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)              |
| <b>Methyl Benzene (108-88-3)</b>             |  |
| LC50 fish 1                                  | 15.22 - 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| EC50 Daphnia 1                               | 5.46 - 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])               |
| EC50 other aquatic organisms 1               | > 433 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)            |
| LC50 fish 2                                  | 12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])                |
| EC50 Daphnia 2                               | 11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)                               |
| EC50 other aquatic organisms 2               | 12.5 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata [static])    |
| <b>Dimethylbenzene (1330-20-7)</b>           |  |
| LC50 fish 1                                  | 13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])          |
| EC50 Daphnia 1                               | 3.82 mg/l (Exposure time: 48 h - Species: water flea)                                  |
| LC50 fish 2                                  | 2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])       |
| EC50 Daphnia 2                               | 0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)                           |
| <b>2-Methylbutane (78-78-4)</b>              |  |
| EC50 Daphnia 1                               | 2.3 mg/l (Exposure time: 48 h - Species: Daphnia magna)                                |

# F 15 O Race Fuel

## Safety Data Sheet

| <b>Tetraethylplumbane (78-00-2)</b> |  |
|-------------------------------------|--|
| LC50 fish 1                         | 84 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)   |
| EC50 Daphnia 1                      | 0.085 mg/l (Exposure time: 48 h - Species: Artemia salina)     |
| LC50 fish 2                         | 19.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas) |

| <b>2,2,4 Trimethylpentane (540-84-1)</b> |   |
|--|---|
| LC50 fish 1                              | .11 mg/l (Exposure time: 96 h – Species: Oncorhynchus Mykiss [Rainbow Trout]) |
| EC50 Daphnia 1                           | .4 mg/l (Exposure time: 48 h - Species: Daphnia magna [Water Flea])           |

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

| <b>2-Methoxy-2-Methylpropane (1634-04-4)</b> |                               |
|--|-------------------------------|
| BCF fish 1                                   | (no bioaccumulation expected) |
| Log Pow                                      | 1.06 (at 23 °C)               |

| <b>Methyl Benzene (108-88-3)</b> |      |
|----------------------------------|------|
| Log Pow                          | 2.65 |

| <b>Dimethylbenzene (1330-20-7)</b> |             |
|------------------------------------|-------------|
| BCF fish 1                         | 0.6 - 15    |
| Log Pow                            | 2.77 - 3.15 |

| <b>2-Methylbutane (78-78-4)</b> |           |
|---------------------------------|-----------|
| Log Pow                         | 3.2 - 3.3 |

| <b>Tetraethylplumbane (78-00-2)</b> |                 |
|-------------------------------------|-----------------|
| BCF fish 1                          | 92 - 3189       |
| Log Pow                             | 4.32 (at 20 °C) |

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

|                                |   |
|--------------------------------|---|
| Waste disposal recommendations | : Dispose of contents/container in accordance with local/regional/national/international regulations.   |
| Product                        | : The products should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company. |
| Contaminated Packaging         | : Empty Remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on the empty drum.  |

## SECTION 14: Transport information

In accordance with DOT

|   |   |
|---|---|
| Transport document description                    | : UN1203 Gasoline includes gasoline mixed with ethyl alcohol, with not more than 10% alcohol, 3, II |
| UN-No.(DOT)                                       | : 1203  |
| DOT NA no.  | : UN1203  |
| DOT Proper Shipping Name                          | : Gasoline<br>includes gasoline mixed with ethyl alcohol, with not more than 10% alcohol            |
| Department of Transportation (DOT) Hazard Classes | : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120                                     |



# F 15 O Race Fuel

## Safety Data Sheet

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger

DOT Special Provisions (49 CFR 172.102) : 144 - If transported as a residue in an underground storage tank (UST), as defined in 40 CFR 280.12, that has been cleaned and purged or rendered inert according to the American Petroleum Institute (API) Standard 1604 (IBR, see 171.7 of this subchapter), then the tank and this material are not subject to any other requirements of this subchapter. However, sediments remaining in the tank that meet the definition for a hazardous material are subject to the applicable regulations of this subchapter.  
177 - Gasoline, or, ethanol and gasoline mixtures, for use in internal combustion engines (e.g., in automobiles, stationary engines and other engines) must be assigned to Packing Group II regardless of variations in volatility.  
B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.  
B33 - MC 300, MC 301, MC 302, MC 303, MC 305, MC 306, and DOT 406 cargo tanks equipped with a 1 psig normal vent used to transport gasoline must conform to Table I of this Special Provision. Based on the volatility class determined by using ASTM D 439 and the Reid vapor pressure (RVP) of the particular gasoline, the maximum lading pressure and maximum ambient temperature permitted during the loading of gasoline may not exceed that listed in Table I.  
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.  
T4 - 2.65 178.274(d)(2) Normal.....178.275(d)(3)

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Packaging Non Bulk (49 CFR 173.xxx) : 202

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : E - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length, but is prohibited from carriage on passenger vessels in which the limiting number of passengers is exceeded.

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### 2-Methoxy-2-Methylpropane (1634-04-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on SARA Section 313 (Specific toxic chemical listings)

|                          |  |
|--------------------------|--|
| EPA TSCA Regulatory Flag | T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA. |
|--------------------------|--|

|                                       |       |
|---------------------------------------|-------|
| SARA Section 313 - Emission Reporting | 1.0 % |
|---------------------------------------|-------|

#### Methyl Benzene (108-88-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on SARA Section 313 (Specific toxic chemical listings)

#### Methyl Benzene (108-88-3)

|                                       |       |
|---------------------------------------|-------|
| SARA Section 313 - Emission Reporting | 1.0 % |
|---------------------------------------|-------|

# F 15 O Race Fuel

## Safety Data Sheet

### Dimethylbenzene (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Listed on SARA Section 313 (Specific toxic chemical listings)

|                                       |       |
|---------------------------------------|-------|
| SARA Section 313 - Emission Reporting | 1.0 % |
|---------------------------------------|-------|

### Tetraethylplumbane (78-00-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Listed on SARA Section 302 (Specific toxic chemical listings)

|  |     |
|--|-----|
| SARA Section 302 Threshold Planning Quantity (TPQ) | 100 |
|--|-----|

### 2,2,4 Trimethylpentane (540-84-1)

|                      |                                    |
|----------------------|------------------------------------|
| SARA 311/312 Hazards | Fire Hazard<br>Acute Health Hazard |
|----------------------|------------------------------------|

|                            |                                    |
|----------------------------|------------------------------------|
| CERCLA Reportable Quantity | 1000 Lbs<br>2,2,4-Trimethylpentane |
|----------------------------|------------------------------------|

|                              |  |
|------------------------------|--|
| Sara 302 Reportable Quantity | This material does not contain any components with a SARA 302 RQ |
|------------------------------|--|

|                                      |   |
|--------------------------------------|---|
| SARA 302 Threshold Planning Quantity | No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302. |
|--------------------------------------|---|

|                              |   |
|------------------------------|---|
| SARA 304 Reportable Quantity | This material does not contain any components with a section 304 EHS RQ |
|------------------------------|---|

|                     |  |
|---------------------|--|
| SARA 13 Ingredients | This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) report levels established by SARA Title III, Section 313. |
|---------------------|--|

## 15.2. US State regulations

### Methyl Benzene (108-88-3)

|   |   |   |   |                                   |
|---|---|---|---|-----------------------------------|
| U.S. – California - Proposition 65 - Carcinogens List | U.S. – California - Proposition 65 - Developmental Toxicity | U.S. – California - Proposition 65 - Reproductive Toxicity - Female | U.S. – California - Proposition 65 - Reproductive Toxicity – Male | No significance risk level (NSRL) |
|   | Yes   | Yes   |   |                                   |

### 2-Methoxy-2-Methylpropane (1634-04-4)

U.S. - Massachusetts - Right To Know List  
U.S. - Minnesota - Hazardous Substance List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### Methyl Benzene (108-88-3)

U.S. - Massachusetts - Right To Know List  
U.S. - Minnesota - Hazardous Substance List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### Dimethylbenzene (1330-20-7)

U.S. - Massachusetts - Right To Know List  
U.S. - Minnesota - Hazardous Substance List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### 2-Methylbutane (78-78-4)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### Tetraethylplumbane (78-00-2)

U.S. - Massachusetts - Right To Know List  
U.S. - Minnesota - Hazardous Substance List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### 2,2,4 Trimethylpentane (540-84-1)

# F 15 O Race Fuel

## Safety Data Sheet

U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### SECTION 16: Other information

Full text of H-phrases:

|                           |   |
|---------------------------|---|
| Acute Tox. 1 (Dermal)     | Acute toxicity (dermal) Category 1                                |
| Acute Tox. 2 (Inhalation) | Acute toxicity (inhalation) Category 2                            |
| Acute Tox. 1 (Oral)       | Acute toxicity (oral) Category 1                                  |
| Acute Tox. 4 (Dermal)     | Acute toxicity (dermal) Category 4                                |
| Acute Tox. 4 (Inhalation) | Acute toxicity (inhalation) Category 4                            |
| Aquatic Acute 1           | Hazardous to the aquatic environment - Acute Hazard Category 1    |
| Aquatic Chronic 1         | Hazardous to the aquatic environment - Chronic Hazard Category 1  |
| Asp. Tox. 1               | Aspiration hazard Category 1                                      |
| Flam. Liq. 1              | Flammable liquids Category 1                                      |
| Flam. Liq. 2              | Flammable liquids Category 2                                      |
| Flam. Liq. 3              | Flammable liquids Category 3                                      |
| Flam. Liq. 4              | Flammable liquids Category 4                                      |
| Repr. 1A                  | Reproductive toxicity Category 1A                                 |
| Repr. 2                   | Reproductive toxicity Category 2                                  |
| Skin Irrit. 2             | Skin corrosion/irritation Category 2                              |
| STOT RE 2                 | Specific target organ toxicity (repeated exposure) Category 2     |
| STOT SE 3                 | Specific target organ toxicity (single exposure) Category 3       |
| H224                      | Extremely flammable liquid and vapor                              |
| H225                      | Highly flammable liquid and vapor                                 |
| H226                      | Flammable liquid and vapor  |
| H227                      | Combustible liquid  |
| H300                      | Fatal if swallowed  |
| H304                      | May be fatal if swallowed and enters airways                      |
| H310                      | Fatal in contact with skin  |
| H312                      | Harmful in contact with skin                                      |
| H315                      | Causes skin irritation  |
| H330                      | Fatal if inhaled  |
| H332                      | Harmful if inhaled  |
| H336                      | May cause drowsiness or dizziness                                 |
| H360                      | May damage fertility or the unborn child                          |
| H361                      | Suspected of damaging fertility or the unborn child               |
| H373                      | May cause damage to organs through prolonged or repeated exposure |
| H400                      | Very toxic to aquatic life  |
| H410                      | Very toxic to aquatic life with long lasting effects              |

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*

**Trade Secret Provision:** *In accordance with OSHA regulations and policies, the specific percentages and specific names of certain chemicals are being designated a trade secret and are not disclosed herein. In compliance with current regulations, this SDS provides the necessary properties and effects of the chemicals listed for this product. In cases of medical emergency, medical personnel can contact the emergency number listed and obtain the specifics of these chemicals. Should this need arise, we will request the attending physician provide to us, at such time as appropriate, a letter stating the medical necessity and a signature of confidentiality for the obtained information.*